

PCTWORLD INTELLECTUAL PRO
International

INTERNATIONAL APPLICATION PUBLISHED UNDER



(51) International Patent Classification⁶ :
B65B 1/04, 3/04

A1

(11)

WO 9608412A1

(43) International Publication Date: 21 March 1996 (21.03.96)

(21) International Application Number: PCT/US95/05138

(22) International Filing Date: 26 April 1995 (26.04.95)

(30) Priority Data:

08/305,637 14 September 1994 (14.09.94) US
08/419,499 10 April 1995 (10.04.95) US

(71)(72) Applicant and Inventor: MESHBERG, Philip [US/US];
Apartment 602, 2770 South Ocean Boulevard, Palm Beach,
FL 33480 (US).

(74) Agents: BRAINARD, Charles, R. et al.; Kenyon & Kenyon,
1025 Connecticut Avenue, N.W., Washington, DC 20036
(US).

(81) Designated States: AM, AU, BB, BG, BR, BY, CA, CN, CZ,
EE, FI, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR,
LT, LV, MD, MG, MN, MW, MX, NO, NZ, PL, RO, RU,
SD, SG, SI, SK, TJ, TT, UA, UG, UZ, VN, European patent
(AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA,
GN, ML, MR, NE, SN, TD, TG), ARIPO patent (KE, MW,
SD, SZ, UG).


Published

*With international search report.
With amended claims.*

(54) Title: DISPENSER AND METHOD OF ITS USE

(57) Abstract

A directional dispensing package (1) including a retaining opening into which a modular pump (12) is snap-fit by inserting the modular pump (12) through an open end of the package. The package (1) is also provided with a dispensing actuator locking and sealing mechanism (23). The package (1) is filled through its open end, and then the bottom portion (217) is sealingly affixed to the package (1).



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

DISPENSER AND METHOD OF ITS USE

This application is a continuation-in-part of U.S. Patent Application Serial No. 08/305,637, filed September 14, 1994, which application is a continuation-in-part of U.S. Patent Application Serial Nos. 08/163,787, filed December 9, 1993 and
5 08/222,975, filed April 5, 1994 as a division of U.S. Patent Application Serial No. 07/887,032, now U.S. Patent No. 5,305,810.

Background of the Invention

Field of the Invention

10 The present invention relates to a complete dispensing package designed to be shipped as an assembled unit to a liquid product marketer, for subsequent filling. The dispensing package is easily filled and bottom sealed with a minimal number of automatic assembly steps. The package of the present invention also includes structure to provide an air seal to the dispensing nozzle and lock the dispensing actuator when
15 it is not in use, and provides a tamper-resistant package. The dispensing package further includes a bottom sealing mechanism adapted for easy assembly, effective sealing, and which allows stacking of the dispensing package upon another dispensing package. The dispensing package may include in one embodiment a dip tube integral with the container portion, which allows for easy filling and assembly. The bottom
20 sealing assembly in another embodiment has mounted integrally thereon a dip tube assembly. This configuration ensures that air will be purged from the dip tube after filling, thereby aiding in priming of the pump. The present invention can also include

a device for allowing dispensing in an inverted position of the dispenser. An embodiment of the invention may also include a mounting cup for mounting the pump to the package without the need for screw threads or crimping. The device of the present invention may also include an element for sealing the spray orifice to prevent drying of the contents of the package within the spray orifice, thereby preventing clogging.

Description of the Related Art

U.S. Patent No. 5,158,211 discloses a dispensing package including a modular pump which is assembled into a dispensing package using a snap fit, such that the dispensing pump is permanently retained in the package. In the device disclosed in Patent No. 5,158,211, the package is filled through an opening at the top of the package. After filling, the pump is attached to the package, either by snap-fitting the pump structure into a retaining opening, or by adding the pump to the package using a conventional screw-cap mounting. Accordingly, in the device of Patent No. 5,158,211, the assembled pump structure and the package must be shipped unassembled to a filling and assembly site, where the package is filled and the pump is then assembled to the package. The invention of Patent No. 5,158,211 also includes a mechanism for sealing the outlet nozzle when the dispenser is not in use, and a mechanism for making the dispenser tamper-resistant, to thereby prevent placing any foreign substances or liquids into the package after it is sealed, and also to prevent accidental discharge of liquid. The mechanism for sealing the dispensing orifice prevents drying of the contents of the container in the spray orifice, thereby preventing clogging of the spray orifice. However, the device of Patent No. 5,128,211 requires that the actuator be rotated to a non-dispensing position for the sealing device to seal the orifice. Furthermore, the device of that patent has a break-away tab for the dispensing position. Such a break-away tab leaves an opening in the actuator shroud which can be the repository for dirt or dust.

U.S. Patent No. 5,305,810 describes a method and apparatus for filling a dispensing package with a highly viscous product. In the method of that patent, the package is filled through a dip tube structure which is inserted into the package prior to filling.

5 U.S. Patent No. 5,392,962, the disclosure of which is incorporated herein by reference, discloses two designs of a pump which is constructed entirely of a plastic material, to make the pump easily recyclable.

Summary of the Invention

10 The present invention is a package-dispensing unit combination designed for easy filling and post-filling assembly, and which can be efficiently shipped to a liquid product producer and to a post-filling marketer. The device of the present invention is especially suitable for promotional purposes, since the liquid product producer need only fill the package and snap on a bottom piece to the package, which may be labeled
15 before or after the filling process. The device of the present invention is ideally suited for allowing directional dispensing of liquid products. The device is thus particularly suited to a quick-turnaround filling and marketing operation, and the assembled and filled packages can be shipped in the same cartons as the unfilled packages were shipped to the liquid product producer. Accordingly, the present invention eliminates
20 waste in carton usage, preventing the need to use different cartons for the containers, pumps and the filled package.

In one embodiment of the present invention, a modular pump is permanently snap-fit or sonically welded in a leak-proof manner into an opening in a retaining wall in the top of the dispensing package, by inserting the pump into either the open
25 bottom or the open top of the package. An actuator can then be assembled onto the package, which package can include a tamper-evidencing feature, as well as structure for locking and sealing the outlet nozzle in a non-dispensing position when not in use. The package can then be shipped to a filling site or to a liquid product producer for filling, final assembly and labelling. At a filling site, the package is inverted, filled
30 from the open bottom, and then a bottom piece is snapped in sealing engagement into

the open bottom of the package. The bottom piece can optionally be ultrasonically welded, or sealed with an adhesive, to the package, in such a way that the bottom is permanently retained on the package in a leak-proof manner.

5 One embodiment of the present invention includes a mechanism for preventing tampering with the contents of the package after it is sealed, and for preventing accidental discharge of the liquid. This feature includes constructing the package so that it is completely sealed after filling. In addition, a snap-off tab is included near the actuator which indicates whether the actuator of the device has been used previously. Also, the device includes a limit stop for preventing actuation of the
10 actuator when locked in a non-dispensing position.

The present invention can be constructed entirely of a plastic material, to make it particularly suitable to recycling. The package can include a spring located between the actuator and the retaining wall. This spring can be constructed of plastic -- so that the entire package can be recycled as a unit -- or can be constructed of metal -- so that
15 the metal spring can be removed from the package easily by simply dislodging the actuator. Both configurations of the present invention make the package easy to recycle.

The present invention includes an embodiment with a dip tube structure which is integrally molded with the package. This construction allows easy assembly and
20 filling of the package, particularly filling the package through the dip tube. As a result, the product is especially useful in dispensing highly viscous products.

The present invention includes several specific structures for the bottom portion which is placed on the package after filling. The construction of this bottom portion allows the package to be easily assembled after filling, yet ensures proper sealing of
25 the package against leakage. The bottom portion can be configured to allow easy stacking of the dispensing package.

The dip tube structure in one embodiment of the present invention ensures that air in the dip tube is purged during the filling and final assembly process, thereby assisting in easing priming of the pump. This is accomplished by forming the dip tube

structure integrally with the bottom structure. This arrangement therefore is very useful when it is desired to dispense viscous products from the dispenser.

In another embodiment of the present invention, a mounting cup is used to secure the pump to the package, and the mounting cup is structured in a manner similar to the bottom of the package. This design obviates the need for either a screw-threaded mounting cup for mounting the pump to the package, or the use of conventional crimping techniques. The mounting cup of the present invention may be easily snapped on, while still providing effective sealing of the contents within the package.

The device of the present invention can include several different designs of an element for allowing inverted dispensing from the package. The inverted dispensing device can be adapted to a dip tube which is integral with the package bottom, or a dip tube which is integral with the package. Finally, the device of the present invention can include several different types of elements for sealing the spray orifice on the actuator, which elements do not present any open recesses for the collection of dirt or dust.

Brief Description of the Drawings

Other objects and advantages of the invention will be apparent from the specification and claims, when considered in connection with the attached sheets of drawings, illustrating one form of the invention, wherein like characters represent like parts and in which:

Fig. 1 is a cross-sectional view of one embodiment of the present invention, with the pump inserted and the bottom closure sealed;

Figs. 2a and 2b show detail cross-sectional views of the pump and retaining opening of the present invention, showing the energy director feature for sonic welding;

Figs. 3a and 3b show detail cross-sectional views of the lower end of the container and the bottom portion which is secured to the container of the present invention, showing the energy director feature;

Figs. 4-6 are perspective views of the actuator and locking mechanisms of the present invention, wherein Fig. 4 includes a partial cross-sectional view;

Fig. 7 shows a front view of the container of the present invention, including a second embodiment of the mechanism for attaching the bottom portion to the container.

Fig. 8 is a bottom view of the container of Fig. 7;

Fig. 9 is a detail view of the retaining mechanism of Figs. 7-8;

Fig. 10 is a detail cross-sectional view of the lower end of the container of Figs. 7-9 and the bottom portion;

Fig. 11 is a cross-sectional view of a second embodiment of the present invention using a spring between the actuator and the container, with the pump inserted and the bottom closure sealed;

Fig. 12 is a cross-sectional view of a third embodiment of the dispensing package of the present invention in which the dispensing package includes an integrally-molded dip tube structure;

Fig. 13 is a cross-sectional detail view of the bottom of a third embodiment of the bottom portion of the dispensing package of the present invention, in an unassembled exploded view;

Fig. 14 is a detail cross-sectional view of the rim seal of the bottom portion of the dispensing package of the embodiment of Fig. 13;

Fig. 15 is a cross-sectional view of a fourth embodiment of the bottom portion of the present invention;

Fig. 16 is a detail view of the embodiment of Fig. 15, showing the manner in which stacking is accomplished;

Fig. 17 is a side view of a package used with the embodiment of Figs. 15-16;

Fig. 18 is a cross-sectional view of a fourth embodiment of the present invention;

Fig. 19 is a cross-sectional view of a fifth embodiment of the present invention;

Fig. 20 is a cross-sectional view of a sixth embodiment of the present invention;

Fig. 21 is an exploded, cross-sectional view of a seventh embodiment of the present invention;

Fig. 22 is a detail, cross-sectional view of the connection between the mounting cup and the package of the embodiment of Fig. 21;

5 Fig. 23 is a detail, cross-sectional view of the connection between the bottom and the package of the embodiment of Fig. 21;

Fig. 24 is a cross-sectional view of an assembled package according to the embodiment of Fig. 21;

10 Fig. 25 is a top view of the actuator and mounting cup of the embodiment of Fig. 21;

Fig. 26 is a partial cross-section of the view of Fig. 25;

Fig. 27 is a perspective view of the actuator and mounting cup of the embodiment of Fig. 21;

15 Fig. 28 is a cross-sectional view of an eighth embodiment of the present invention;

Fig. 29 is an exploded view of a inverted dispensing device of the present invention;

Fig. 30 is an assembled, cross-sectional view of the inverted dispensing device of Fig. 29;

20 Fig. 31 is a cross-sectional view of the embodiment of Fig. 12 using the inverted dispensing device of Figs. 29-30;

Figs. 32 is a cross-sectional view of the upper end of the container of the present invention, showing two positions of the spray orifice sealing device;

25 Fig. 33 is a cross-sectional view of the spray orifice sealing device of the present invention;

Fig. 34 is a front view of the spray orifice sealing device of the present invention;

Fig. 35 is a top cross-sectional view of the upper end of the container of the present invention, showing the spray orifice sealing device;

Fig. 36 is a front view of the of the upper end of the container of the present invention, showing the spray orifice sealing device.

Detailed Description of the Invention

5 A first embodiment of the present invention is shown in cross-sectional view, in a sealed condition, in Fig. 1. The present invention includes a package 1 which includes a container portion 2 and an upstanding wall portion 3. Upstanding wall portion 3 includes a tamper evident tab portion 4, connected to the upstanding wall portion 3 by a snap-away or tear-away joint 7. Joint 7 is originally molded to
10 integrally connect tab portion 4 to upstanding wall 3, but is designed to be of sufficient thinness so that an end user can ultimately break the joint 7 so that the tab portion 4 can be removed from sleeve portion 3 to uncover nozzle 9 on actuator 6 when it is desired to first use the dispenser 1. Upstanding wall 3 can include a recess 8 intended to facilitate movement of an actuator nozzle 9 within the upstanding wall
15 3. Although shown as being vertically oriented in Figs. 1, tab portion 4 could also be oriented in a horizontal direction, with the joint 7 being disposed vertically at one end of the tab 4.

Container portion 2 and upstanding wall 3 are separated by a retaining wall 10 which includes a retaining opening 11 used to secure a pump 12 in the package 1.
20 Pump 12 can be of any conventional design. Pump 12 includes a retention flange 13 for limiting the amount of inward movement of the pump 12 into the container 1 and for providing a surface for an energy director 15 to adhere during a process of sonic or ultrasonic welding. Alternatively, pump could include a retention groove which retains the pump 12 in the package 1 via a snap-fit engagement with retaining
25 wall 10. Pump 12 is inserted into retaining opening 11 through the lower end 16 of container portion 2 or from the upper end including the upstanding wall 3, which is initially open.

Figs. 2a and 2b show detail views of the pump 12, pump flange 13, retaining wall 10 and energy director 15. Energy director 15 is a molded ridge which -- when
30 excited by sonic or ultrasonic vibration of container 2 -- causes retaining wall 10 and

flange 13 to weld together, thereby permanently retaining pump 12 in container portion 2 and sealing the upper end of the container portion 2.

Figs. 3a and 3b show detail views of the mechanism whereby a bottom portion 17 is attached to lower end 16 of container portion 2. Lower end 16 includes a tapered portion 18 which is shaped so as to fit into a retaining groove 19 in bottom portion 17. Retaining groove 19 or lower end 16 contains, at its lower end, an energy director 20 used to secure and seal bottom portion 17 to the lower end 16 of container portion 2. As with energy director 15, energy director 20 is a molded ridge which when excited by sonic or ultrasonic vibration of container 2 causes lower end 16 and bottom portion 17 to weld together, thereby permanently retaining bottom portion 17 on container portion 2 and sealing the lower end of the container portion 2.

Figs. 4-6 show the particular features of the actuator 6 of the present device, and the particular locking and retaining features of the upstanding wall 3. In Fig. 4, the forward portion of actuator 6 is shown in cross-sectional view, to show the manner in which the nozzle 9 is sealed in a non-dispensing position. Actuator 6 includes a projecting portion 21 which is used to rotate actuator 6 from a dispensing to a non-dispensing position, and which also acts to prevent downward movement of actuator 6 when actuator 6 is in a non-dispensing position. Upstanding wall 3 includes a limit stop 22 which prevents actuator 6 from moving downward -- and thus dispensing material from pump 12 -- via engagement with limit stop 22 (See Fig. 4). The position of the actuator 6 shown in Fig. 4 is the position in which the actuator 6 is kept before the tab 4 is removed from upstanding wall 3. In this position, nozzle 9, which includes a slightly projecting tip, is snapped into a vertical groove 23. Groove 23 acts to retain nozzle 9 and actuator 6 in a non-dispensing position, and also seals the nozzle 9 against the incursion of air into the nozzle 9 orifice. Rotating actuator 6 in the direction indicated by arrow S places the actuator 6 and nozzle 9 into a spraying or dispensing position. In this position (shown in Figs. 5 and 6) projecting portion 21 is in alignment with recess 8. In this position, nozzle 9 is aligned with opening 25 which is formed when tab 4 is removed. As seen by comparing Figs. 5 and 6, projecting portion 21 travels within recess 8 upon downward actuation of

actuator 6, allowing dispensing of material through nozzle 9 via pump 12. Rotating actuator 6 in the direction indicated by arrow L initiates a locking position, in which nozzle 9 is snapped into groove 23. Indication that nozzle 9 is properly in a non-dispensing position can be provided via a bead 26, which can coact with a bead on the outer circumferential surface of actuator 6, thereby providing an audible "snapping" sound when the beads slide over one another.

Figs. 7 and 8 show a front and bottom view of the container portion 2 of the present invention, which includes a second embodiment of a mechanism for securing the bottom portion 17 to the container portion 2. Lower end 16 of container portion 2 contains a series of angled tabs 30. Angled tabs 30 are designed to fit into groove 19 in bottom portion 17. Upper end of angled tabs 30 include a generally horizontal surface 31a intended to snap into a horizontally projecting portion 31 on bottom portion 17. Angled tabs 30 and horizontal surface 31a allow bottom portion 17 to be secured horizontally to container portion 2 to thereby ensure good sealing of the bottom portion 17 to the container portion 2 through its entire periphery.

The transition area between container portion 2 and upstanding wall 3 can contain a shoulder 32. Shoulder 32 is useful for an assembly and filling operation of the present invention, as will be described below.

As shown in Fig. 11, the pump spring 50 of the present invention can be located between the retaining wall 10 and the actuator 6, as described in U.S. Patent No. 5,392,962, the substance of which is incorporated herein by reference. In the configuration of Fig. 11, the spring 50 can be made of a plastic material, making the entire package recyclable, or the spring 50 can be metallic. If the spring 50 is metallic, the package 1 is still easily recyclable, since the metallic spring 50 is easily removed from the package by simply dislodging the actuator 6 and removing the spring 50. The package 1 of the present invention may also be made of a biodegradable plastic material, so that it has less of an environmental impact.

The method of using the device of Figs. 1-11 is as follows. The container portion 2 is molded as an integral unit with upstanding wall 3 and retaining wall 10. Container portion 2 is inverted, and preferably inserted into a holding or restraining

mechanism which interacts with shoulder 32 to restrain container portion 2 in an inverted position. Next, pump 12 is inserted into either the open end of lower end 16 or upper end including upstanding wall 3 (as described, for example, in U.S. Patent No. 5,158,211), so that the pump 12 fits through retaining opening 11 until flange 13 abuts retaining wall 10, or until the pump is press-fit into retaining opening 11. If retaining wall 10 contains an energy director 15, container portion 2 is sonically or ultrasonically excited so that energy director 15 welds retaining wall 10 and flange 13 in a sealing relation. Actuator 6 can then be inserted onto the outlet stem 40 of pump 12.

The container portion 2 thus assembled is shipped together with bottom portion 17 in an unassembled condition to a filling and assembly location. When it is desired to fill package 1, container portion 2 is again inverted, preferably by engaging shoulder 32 with a holding device. Container portion 2 is then filled with liquid product through open lower end 16. Bottom portion 17 is then placed on lower end 16. If bottom portion 17 contains an energy director 20, container portion 2 is sonically or ultrasonically excited so that energy director 20 welds bottom portion 17 and lower end 16 in a sealing relation. In the case of lower end 17 including angled tabs 30, bottom portion 17 is inserted onto lower end 16 until portion 31 snaps under angled tabs 30.

After bottom portion 17 is sealed to lower end 16, the package 1 can be labelled and shipped to an end user, or alternatively, package 1 can be labelled before the container portion 2 is shipped to the liquid product marketer. Upon receiving package 1, the customer breaks off tab 4, and then when dispensing is desired, rotates actuator 6 to the position shown in Fig. 5. Downward actuation of actuator 6 dispenses liquid product from package 1, through nozzle 9.

Fig. 12 shows an embodiment of the present invention in which a dip tube structure 160 is integrally molded with container portion 102. Retaining wall 110 in the embodiment of Fig. 12 is integrally molded with dip tube structure 160 to form a one-piece unit. Dip tube structure 160 includes a venting hole or slot 161, which allows air to escape from container during filling, when filling is accomplished

through dip tube structure 160 after bottom portion 117 is secured to container portion 102. The method of filling container 102 through dip tube structure 160 and subsequently assembling pump 12 on container 102 is described in detail in U.S. Patent No. 5,305,810, the disclosure of which is incorporated herein by reference. The configuration shown in Fig. 12 incorporating an integrally molded dip tube structure 160 is particularly useful for viscous products, for which there may be difficulty in priming the pump, as described in U.S. Patent No. 5,305,810. The container 101, of course, may also be filled through the bottom, as described hereinabove, after insertion and securement of the pump 112 onto container portion 102. Pump 112 may be secured to container portion 102 either by a conventional snap or interference fit between the exterior of pump 102 and the retaining wall 110 or dip tube structure 160, or by ultrasonic welding using energy directors, as discussed hereinabove.

Figs. 13 and 14 show an alternative embodiment container portion 202 and bottom portion 217 used in the present invention. The bottom portion 217 in the embodiment of Figs. 13 and 14 is particularly effective in ensuring a leakproof seal at the bottom of container portion 202. Bottom portion 217 includes an interior piston portion 280, which slides in and seals against an interior sealing surface 281 of container portion 202. Interior sealing surface 201 can be slightly inset from interior surface 282 of container portion 202. Interior piston portion 280 includes a tapered sealing surface 283 extending at an angle ϕ from vertical. Tapered sealing surface 283 ensures a good leakproof seal of interior piston portion 280 against interior sealing surface 281. Container portion 202 also includes, at its lower end, angled snap rim 284 extending around the entire circumference of container portion 202. Snap rim 284 includes an upper snap surface 285. Bottom portion 217 includes an exterior snap flange 286 which is used to secure and seal bottom portion 217 to container portion 202. Snap flange 286 includes, at its upper end, an angled snap lip 287 extending around the entire circumference of snap flange 286, and a series of snap fingers 288 spaced circumferentially around the interior of snap flange 286. Snap fingers 288 engage with snap surface 285 on snap rim 284 to thereby secure bottom portion 217 to container portion 202. Snap lip 287 generally contacts the exterior of container

portion 202 to thereby ensure a good leakproof seal of bottom portion 217 to container portion 202. Bottom portion 217 may include openings 289 to allow proper molding of snap fingers 288 on snap flange 286.

During assembly, bottom portion 217 is slid onto container portion 202 in direction D. As bottom portion slides in direction D, sealing surfaces 281 and 283 engage and seal against one another. As bottom portion 217 moves further in direction D, first snap lip 287 and then snap fingers 288 move around snap rim 284. After snap fingers 288 move around snap rim 284, snap fingers 288 snap into engagement with snap surface 285 to secure bottom portion 217 to container portion 202, and snap lip 287 snaps into engagement with the exterior of container portion 202. As a result, bottom portion 217 is sealed and secured to container portion 202.

Figs. 15 and 16 show an alternative configuration of the bottom portion which allows the container to be easily stacked. Bottom portion 317 in the embodiment of Figs. 15 and 16 has a stacking flange 393 which is shaped so as to receive upstanding wall 3, as shown in Fig. 16. Accordingly, as shown in Fig. 16, a first container 201' may be easily stacked and secured upon a second container 201".

Fig. 17 shows an advantageous packaging arrangement for packaging and shipping stacked containers 201', 201" of the type shown in Figs. 15 and 16. Package 390 is wrapped around a series of stacked containers 201', 201" and includes a tear-strip 391 for unwrapping package 390 and gaining access to containers 201', 201".

Another embodiment of the present invention is shown in cross-sectional view, in a sealed condition, in Fig. 18. The present invention includes a package 1 which includes a container portion 2. Container portion 2 includes a retaining opening 11 used to secure a pump 12 in the package 1. Pump 12 can be of any conventional design. Pump 12 includes a retention flange 13 for limiting the amount of inward movement of the pump 12 into the container 1. Retention flange 13 retains the pump 12 in the package 1 via a snap-fit engagement with retaining opening 11. Pump 12 is inserted into retaining opening 11 through the upper end of container portion 2. Pump 12 or container portion 2 can include energy directors for sonically welding pump 12 to container portion 2.

A bottom portion 17 is attached to lower end 16 of container portion 2. The mechanism for retaining bottom portion 17 to lower end 16 is described in detail above. Bottom portion 17 has molded integrally therewith a dip tube structure 160, which includes an upwardly-projecting tube 170, and a lower end 171 integrally molded with bottom portion 17. Lower end 171 includes one or more openings 172 which allow fluid to flow from the interior 200 of container portion 2 to the interior of tube 170.

Mounted to the exterior of the pump 12 and within the interior of container portion 2 is an insert 300. Insert 300 includes an exterior flange 301 which seals against the interior of container portion 2. Insert 300 also includes a interior flange 302 into which the bottom portion of pump 12 is fit. Interior flange 302 contains, at its bottom, an insertion flaring 303, which is described in detail below. An insert cap 304 is mounted on the upper end of insert 300. Insert 300 includes an inverted dispensing device 305, which is adapted to allow the dispenser 1 to dispense product when the dispenser 1 is in an inverted state. Inverted dispensing device 305 includes an inlet opening 306, a check valve 307, and an outlet opening 308. Outlet opening 308 cooperates with an inverted inlet opening 309 in the housing of the pump 12. Inverted inlet opening 309 is located below or axially inward of the inlet valve (not shown) to pump 12.

The method of using the device of the present invention is as follows. The container portion 2 is molded as an integral unit. Next, pump 12 is snapped or press-fit into retaining opening 11. Actuator 6 can then be inserted onto the outlet stem 40 of pump 12. The insert 300, with insert cap 304 mounted thereon, is then inserted through the bottom 16 of container portion 2 such that it slides along the interior wall of container portion 2 and over the bottom of pump 12.

The container portion 2 thus assembled is shipped together with bottom portion 17 in an unassembled condition to a filling and assembly location. When it is desired to fill package 1, container portion 2 is inverted, preferably by engaging shoulder 32 with a holding device. Container portion 2 is then filled with liquid product through open lower end 16. Bottom portion 17 is then placed on lower end 16. The tube 170

is inserted into the open bottom end 12a of pump 12, and insertion flaring 303 aids in guiding tube 170 into open bottom end 12a. As the tube 170 is inserted into the lower end 16 of filled container 12, liquid product travels into the tube 170, thereby forcing air in tube 170 out through openings 172. Bottom portion 17 is sealed to the lower end 16 of container portion, in any of the ways described above.

In an upright position of package 1, liquid product will be drawn into the openings 172 and up tube 170 in response to a pressure decrease within pump 12. Because the tube 170 is initially filled with liquid product, there is little difficulty in drawing up and purging any air trapped in tube 170, thereby making priming of pump 12 much simpler. Accordingly, the present invention is particularly adapted for use with products which normally make a pump hard to prime, *i.e.*, viscous products.

In an inverted position of package 1, check valve 307 falls away from the sealing surface 310 immediately above inlet opening 306, thereby creating a fluid path from inlet opening 306 to outlet opening 308, and thereby to the interior of pump 12 through inverted inlet opening 309. Upon actuation of actuator 6 in an inverted position, therefore, liquid product will be drawn into pump through inverted inlet opening 309 to allow inverted dispensing.

Fig. 19 shows another embodiment of the present invention. The embodiment of Fig. 19 is identical in structure and operation to the embodiment of Fig. 18, except that there is no inverted dispensing device 305 on the insert 300. Accordingly, the embodiment of Fig. 18 is not adapted to allow dispensing from package 1 when package 1 is in an inverted position.

Fig. 20 shows a further embodiment of the present invention. The embodiment of Fig. 20 is identical in structure and operation to the embodiments of Figs. 18 and 19, except that the embodiment of Fig. 20 does not include insert 300 or any of the structure of insert 300.

Figs. 21-27 show another embodiment of the present invention. The embodiment of Figs. 21-27 is especially useful for larger-size bottles or containers, in which the container portion 402 of the package 401 is made by manufacturing techniques other than injection molding, *e.g.*, the container portion 402 is blow-

molded. The lower end of package 401 is manufactured and assembled in an identical manner to the embodiment of Figs. 12-14 -- i.e., the lower portion of container portion 402 includes a snap rim 284 with a snap surface 285. Similarly, the bottom portion 217 of package 401 is identical to that of Figs. 12-14 -- i.e., bottom portion contains a snap flange 286 with snap lip 287 and a series of snap fingers 288, as well as openings 289 corresponding to snap fingers 288, and also includes an interior piston portion 280 with a sealing surface 283 for sealing on sealing surface 281 of container portion 402.

The embodiment of Figs. 21-27 also includes a mounting cup 417 for mounting a pump 12 to the upper end of container portion 402. Mounting cup 417 includes a retaining wall 410 including a retaining opening 411 used to secure a pump 12 in the mounting cup 417. Pump 12 can be of any conventional design. Pump 12 includes a retention flange 13 for limiting the amount of inward movement of the pump 12 into the retaining opening 411 of the mounting cup 417. Retention flange 13 retains the pump 12 in the mounting cup 417 via a snap-fit engagement with retaining opening 411. Pump 12 is inserted into retaining opening 411 through the upper end of mounting cup 417. Pump 12 or mounting cup 417 can include energy directors for sonically welding pump 12 to mounting cup 417.

The mounting cup 417 in the embodiment of Figs. 21-27 is particularly effective in ensuring a leakproof and easy-to-assemble mounting of pump 12 onto container portion 402 without the need for complicated molding of container portion 402. Mounting cup 417 includes an interior piston portion 480, which slides in and seals against an interior sealing surface 481 of container portion 402. Interior sealing surface 481 can be slightly inset from interior surface 482 of container portion 402. Interior piston portion 480 includes a tapered sealing surface 483 extending at an angle θ from vertical. Tapered sealing surface 483 ensures a good leakproof seal of interior piston portion 480 against interior sealing surface 481. Container portion 402 also includes, at its upper end, angled snap rim 484 extending around the entire circumference of container portion 402. Snap rim 484 includes a lower snap surface 485. Mounting cup 417 includes an exterior snap flange 486 which is used to secure

and seal mounting cup 417 to container portion 402. Snap flange 486 includes, at its upper end, an angled snap lip 487 extending around the entire circumference of snap flange 486, and a series of snap fingers 488 spaced circumferentially around the interior of snap flange 486. Snap fingers 488 engage with snap surface 485 on snap rim 484 to thereby secure mounting cup 417 to container portion 402. Snap lip 487 generally contacts the exterior of container portion 402 to thereby ensure a good leakproof seal of mounting cup 417 to container portion 402. Mounting cup 417 may include openings 489 to allow proper molding of snap fingers 488 on snap flange 486.

The apparatus of Figs. 21-27 can be assembled and filled in one of two ways. First, the pump 12 can be mounted to mounting cup 417 and then mounting cup 417 mounted to container portion 402. Container portion 402 may then be filled through the bottom, as described above, after which bottom portion 217 may be snapped onto container portion 402. Alternatively, the bottom portion 217 could be snapped to container portion 402 first (or, alternatively, the container portion 402 could be made with an integral bottom), the container portion 402 filled through the top, and then mounting cup 417, with pump 12 and actuator 6 already mounted thereon, could be snapped onto container portion 402.

Figs. 25-27 show the details of the element for sealing the nozzle 9 on actuator 6. Upstanding wall 403 has mounted thereon, by way of a hinge connection 440, a sealing finger 404. Hinge connection 440 can be of any known type, including a molded pin on upstanding wall 403 fitting within a hole within the cylindrical portion 441 of sealing finger 404. Cylindrical portion 441 fits within a semi-circular recess 442 in actuator 6. The fit between cylindrical portion 441 and recess 442 ensures that actuator 6 is not rotated such that spray nozzle 9 is not aligned with spray opening 425 in upstanding wall 403. Sealing finger 404, when it is desired to dispense from package 401, is pivoted away from the spray nozzle 9, to the position shown in Figs. 26 and 27. After dispensing, the sealing finger 404 is pivoted towards spray nozzle 9, so that an annular sealing rim 445 engages in an opening adjacent the spray nozzle 9. This engagement seals the nozzle 9 from the encroachment of air or other debris

into spray nozzle 9, thereby preventing clogging of the nozzle 9 between dispensing strokes.

Fig. 28 shows a cross-sectional view of the dispensing package 401 of Figs. 21-27, with the inclusion of an inverted apparatus 560 to allow inverted dispensing from the dispensing package 401. Figs. 29-30 show detail views of the inverted apparatus 560 shown in Fig. 28. Inverted apparatus 560 includes a dip tube adapter 561, a lower valve cage 562, a lower valve ball 563, an upper dip tube 564, an upper valve cage 565 and an upper valve ball 566. The first upper opening 567 of dip tube adapter 561 can be sized so as to securely receive a molded dip tube (as shown in Fig. 31), or so as to receive a conventional dip tube (as shown in Fig. 28) which is inserted into a pump. The second upper opening 568 of dip tube adapter 561 is sized so as to securely receive upper dip tube 564, manufactured of a conventional dip tube material. Upper valve cage 565 and lower valve cage 562 are essentially identical in construction; each includes a conical sealing surface 569 upon which balls 563 or 566 may seal, and projections 570 retaining balls 563 or 566 within valve cages 562 and 565, respectively. Upper valve cage 565 is mounted on the end of upper dip tube 564 opposite the end of upper dip tube 564 mounted in second upper opening 568. Upper valve cage 565 includes tapering 571 in outlet opening 572 for assisting in mounting of upper valve cage 565 on upper dip tube 564. Outlet opening 572 is sized so as to securely receive upper dip tube 564. Lower valve cage 562 fits securely in lower opening 573 of dip tube adapter 561.

In operation of the inverted apparatus 560, in an upright position of a dispenser, upper valve ball 566 seals against the conical sealing surface 569 in upper valve cage 565 under the action of gravity, thereby preventing the inlet of air or liquid into upper dip tube 564 and thereby into dip tube adapter 561 and the dip tube of the dispenser. Lower valve ball 563 is retained by projections 570 in lower valve cage 562, which projections allow liquid in the bottom of the dispenser to be drawn into the dip tube, upon a reduction in pressure in the dip tube, around lower ball valve 563. In an inverted position of the dispenser, lower valve ball 563 seals against the conical sealing surface 569 in lower valve cage 562 under the action of gravity, thereby

preventing the inlet of air or liquid into dip tube through lower valve cage 562. Upper valve ball 566 is retained by projections 570 in upper valve cage 565, which projections allow liquid in the top of the dispenser to be drawn around lower ball valve 563, into the upper dip tube 564, through dip tube adapter 561 and into the dip tube of the dispenser, upon a reduction in pressure in the dip tube of the dispenser. As a result, the inverted apparatus 560 allows dispensing from the dispenser in both upright and inverted positions. The design of the inverted apparatus 560 is such that it is amenable to mass, high-speed assembly, and is adaptable to any number of dip tube sizes and configurations by merely substituting a different-sized dip tube adapter 561 into the assembly. The inverted apparatus 560 also does not require any modifications to the structure of the dip tube, pump or dispenser, and therefore can be easily adapted to any dispenser or pump size or style.

Fig. 31 shows a view of the dispenser of Fig. 12, which includes an integrally molded dip tube structure 160 cooperating with the inverted apparatus 560.

Figs. 32-36 show the features of a spray orifice sealing device of the present invention. Upstanding wall portion 3 has mounted thereon, on opposite sides of the spray opening 25 lugs 905. Lugs 905 have a front opening 906 through which the sealing finger 904 lower end may be inserted. Sealing finger 904 includes a hinge element 907 mounted on a front surface 908 of sealing finger 904. Hinge element 907 includes a flattened surface 909, and other than flattened surface 909 is cylindrical in shape. Lugs 905 define an opening which is cylindrical in shape, except for a flattened section 910. Hinge element 907 therefore rotates in the opening in lugs 905, but snap-locks into the position shown as 904' when the flattened surface 909 interacts with flattened section 910. Sealing finger 904 includes a closure projection 911 which is shaped so as to sealingly fit within the opening surrounding the spray orifice on the actuator. Accordingly, in the position shown as 904 in Fig. 32, the closure portion 911 projects into, and seals, the opening around the spray orifice, preventing air from entering the spray orifice and drying out the liquid in the dispenser. This sealing prevents any potential clogging of the spray orifice. In the position shown as 904' in

Fig. 32, the sealing finger 904 is snapped into a position away from the spray orifice, where the sealing finger 904 will not interfere with the spray from the spray orifice.

5 Sealing finger 904 is designed so that front surface 908 lies flush with the outer surface of upstanding wall 3. In addition, sealing finger 904 is easily inserted into lugs 905, thereby allowing easy interchangeability of sealing finger 904 onto upstanding wall 3, so that sealing fingers 904 having different colors, different closure
10 portion 911 sizes and shapes, etc., may be placed on upstanding wall 3. Furthermore, sealing finger 904 completely fills the spray opening 25 when closure portion 911 is engaged with the spray orifice opening on the actuator so that dirt, sand, or lint does not clog spray opening 25.

It is to be understood that the description above is of preferred embodiments of the present invention, and that it is the claims of the present invention, and not the descriptions above, which define the present invention.

Claims

1. A dispensing package comprising:

an integrally formed container portion (2) comprising:

5 an upstanding wall portion (3), a lower portion (16) and a retaining wall (10), said lower portion (16) containing an open lower end, said retaining wall (10) comprising a retaining opening;

10 a pump structure (12), a circumferential outer surface of said pump structure being formed to be retained in said retaining opening and sealed to said retaining wall (10);

an actuator portion (6) retained upon said pump structure (12); and

15 a bottom portion (17, 117, 217, 317), said bottom portion (17, 117, 217, 317) being formed separate from said container portion (2), said bottom portion being formed to be secured to said lower end (16) and sealed to said lower end (16), whereby said container portion (2) can be filled with a liquid product through said open lower end and said bottom portion (17, 117, 217, 317) sealed to said lower end (16) to seal said liquid product within said container portion.

2. The dispensing package of claim 1, wherein:

5 said upstanding wall portion (3) comprises a groove (23) for retaining and sealing a nozzle (9) on said actuator portion (6), said upstanding wall (3) further comprising a limit stop (22) for preventing downward movement of said actuator portion (3) when said nozzle (9) is retained in said groove (23).

3. The dispensing package of claim 1, wherein:

said upstanding wall portion (3) comprises a removable tab (4) covering a dispensing opening (25) in said upstanding wall (3).

4. The dispensing package of claim 1, further comprising:

a shoulder (32) on said package (1) for supporting said package (1) during an assembly operation and a filling operation.

5. The dispensing package of claim 1, further comprising:

an energy director (15) for providing a seal between said retaining wall (10) and said pump structure (12).

6. The dispensing package of claim 1, further comprising:

an energy director (20) for providing a seal between said bottom portion (17) and said container portion (2).

7. The dispensing package of claim 1, further comprising:

angled tabs (30) on said lower end (16) of said container portion (2), said angled tabs (30) cooperating with a horizontal portion (31) on said bottom portion (17), to thereby ensure that said bottom portion (17) is secured horizontally to said container portion (2).

8. A method of providing a dispensing container comprising the steps of:

providing a package (2) comprising an open lower end (16) and a retaining wall (10) in an upper end, said retaining wall (10) comprising a retaining opening;
providing a pump structure (12);

inserting said pump structure (12) into said retaining opening through said open lower end (16);

filling said package (2) with a fluid product through said open lower end (16);
providing a bottom portion (17, 117, 217, 317); and

attaching said bottom portion (17, 117, 217, 317) to said open lower end (16)
to thereby seal said fluid product in said package (2).

9. The method of claim 1, further comprising the steps of:

providing a spray actuator (6); and

inserting said spray actuator (6) on said pump structure (12).

10. The dispensing package of claim 1, further comprising:
a dip tube structure (160) integrally molded with said retaining wall (10).

11. The dispensing package of claim 10, wherein:
5 said dip tube structure (160) comprises a vent hole (161).

12. A dispensing package comprising:
an integrally formed container portion (2) comprising:
an upstanding wall portion (3), a lower portion and a retaining wall
(10), said lower portion containing an open lower end (16) and a retaining rim (284),
5 said retaining wall (10) comprising a retaining opening;

a pump structure (12), a circumferential outer surface of said pump structure
(12) being formed to be retained in said retaining opening and sealed to said retaining
wall;

an actuator portion (6) retained upon said pump structure (12); and

10 a bottom portion (117, 217), said bottom portion (117, 217) being formed
separate from said container portion (2), said bottom portion (117, 217) being formed
to be secured to said open lower end (16) and sealed to said lower end (16), said
bottom portion (117, 217) comprising a bottom portion inner sealing surface (280)
sealable against an interior of said container portion (2), said bottom portion (117,
15 217) further comprising an outer retaining portion (286) engageable with said retaining
rim (280), whereby said container portion (2) can be filled with a liquid product
through said open lower end (16) and said bottom portion (117, 217) secured and
sealed to said lower end (16) to seal said liquid product within said container portion
(2).

13. The dispensing package of claim 12, wherein:
said bottom portion inner sealing surface (280) is tapered.

14. The dispensing package of claim 12, wherein:

said outer retaining portion (286) comprises snap fingers (288) engaging said retaining rim (284).

15. The dispensing package of claim 14, wherein:

said outer retaining portion (286) comprises a snap lip (287).

16. The dispensing package of claim 15, wherein:

said bottom portion (117, 217) comprises a stacking flange (393) engageable with said upstanding wall portion (3).

17. A dispensing package comprising:

an integrally formed container portion (2) comprising:

a lower portion and a retaining opening (11), said lower portion containing an open lower end (16);

5 a pump structure (12), a circumferential outer surface of said pump structure (12) being formed to be retained in said retaining opening (11); and

a bottom portion (17), said bottom portion (17) being formed separate from said container portion (2), said bottom portion (17) being formed to be secured to said open lower end (16) and sealed to said lower end (16), said bottom portion (17) comprising an integrally-formed dip tube (160), said dip tube comprising an least one opening (172) at an end of said dip tube adjacent said bottom portion (17), whereby said container portion (2) can be filled with a liquid product through said open lower end (16) and said dip tube (160) inserted through said open lower end (16) and said bottom portion (17) sealed to said lower end (17) to seal said liquid product within
10
15 said container portion (2).

18. The dispensing package of claim 17, further comprising:

an insert (300), said insert being secured to a axially inward end of said pump (12).

19. The dispensing package of claim 18, wherein:

said insert (300) comprises an inlet passage (306), an outlet passage (308) and a valve (307), said valve (307) closing said inlet passage (306) in a non-inverted position of said dispensing package (1), said inlet passage (306) and said outlet passage (308) providing fluid communication between an interior of said package (1) and an interior of said pump (12) in an inverted position of said dispensing package (1).

20. The dispensing package of claim 18, wherein:

said insert (300) comprises a flared portion (303) adjacent a lower end of said pump (12), said flared portion (303) assisting insertion of an end of said dip tube (160) into said lower end of said pump (12).

21. A method of providing a dispensing container comprising the steps of:

providing a package (2) comprising an open lower end (16) and a retaining opening (11);

providing a pump structure (12);

inserting said pump structure (12) into said retaining opening (11);

filling said package (2) with a fluid product through said open lower end (16);

providing a bottom portion (17) with an integrally-formed dip tube (160);

inserting said dip tube (160) through said open lower end (16);

engaging an end of said dip tube (160) with said pump structure (12); and

attaching said bottom portion (17) to said open lower end (16) to thereby seal said fluid product in said package (2).

22. The method of claim 21, further comprising the step of:

inserting an insert (300) onto said lower end of said pump structure (12) after said step of inserting said pump structure (12) into said retaining opening (11).

23. An apparatus for securing a pump dispenser to a container comprising a retaining rim, said apparatus comprising:

a central opening (411), said central opening being shaped to receive an outer surface of said pump dispenser (12);

an inner sealing surface (283) sealable against an interior of said container (481); and

5 an outer retaining portion (486) engageable with said retaining rim (484), said outer retaining portion (486) comprising a plurality of snap fingers (488) engageable with said retaining rim (484).

24. The apparatus of claim 23, further comprising:

10 a sealing finger (404, 604) pivotally mounted on an upstanding wall (403, 603), said sealing finger comprising a sealing rim (445).

25. The apparatus of claim 24, wherein:

 said sealing finger (404, 604) pivots about a horizontal axis.

15

26. The apparatus of claim 24, wherein:

 said sealing finger (404, 604) pivots about a vertical axis.

27. The apparatus of claim 24, further comprising:

20 a detent for retaining said sealing finger (404, 604) in a position away from said upstanding wall (403, 603).

28. The apparatus of claim 26, further comprising:

25 a hinge (441), said hinge comprising a radially projecting portion engageable with an actuator (6) to prevent rotation of said actuator (6).

29. A dispensing package comprising:

 a pump dispenser (12), said pump dispenser (12) comprising an outer surface;

a container (402), said container (402) comprising an outlet opening, said container (402) further comprising a annular rim (484) surrounding said outlet opening, said outlet opening comprising an inner surface (481); and

a mounting device (417), said mounting device (417) comprising:

5 (a) central opening (411), said central opening (411) being shaped to fixedly receive said outer surface of said pump dispenser (12);

(b) an inner sealing surface (483) sealable against said inner surface (481); and

10 (c) an outer retaining portion (486) engageable with said annular rim (484), said outer retaining portion (486) comprising a plurality of snap fingers (488) engageable with said retaining rim (484).

30. An apparatus for allowing inverted dispensing from a dispensing container comprising a dip tube, said apparatus comprising:

15 a first valve element (561, 562), said first valve element comprising first and second inlet openings and an outlet opening, said first valve element further comprising a gravity-biased check valve (563), said outlet opening of said first valve element receiving a lower end of said dip tube;

20 a tube (564), an end of said tube (564) being received in said second inlet opening of said first valve element (561, 562); and

a second valve element (565), said second valve element comprising an inlet opening, an outlet opening and a gravity-biased check valve (566), said outlet opening of said second valve element receiving another end of said tube (564).

31. A contamination prevention feature comprising:

an actuator (6) comprising a spray orifice and an orifice opening surrounding said spray orifice;

5 an upstanding wall (3) at least partially surrounding said actuator (6) , said upstanding wall (3) further comprising a spray opening (25);

5 a sealing finger (404, 904), said sealing finger (404, 904) comprising an insert (445, 911), said insert (445, 911) being shaped to sealingly fit within said orifice opening, said sealing finger (404, 904) being pivotally mounted to said upstanding wall (3) so that in a first position of said sealing finger (404, 904) said insert sealingly fits within said orifice opening and covers said spray opening, and so that in a second position of said sealing finger (404, 904), said insert (445, 911) is spaced from said orifice opening and said sealing finger is spaced from said spray opening.

32. The contamination prevention feature of claim 16, wherein:
said sealing finger (404) pivots about a horizontal axis.

33. The contamination prevention feature of claim 16, wherein:
said sealing finger (904) pivots about a vertical axis.

34. The contamination prevention feature of claim 16, further comprising:
a hinge connecting (441) said sealing finger (404) to said upstanding wall (3), at least a portion of said hinge fitting in a recess (442) in said actuator (6) to thereby prevent said actuator (6) from rotating.

35. The contamination prevention feature of claim 16, further comprising:
a hinge (907) and at least one lug (905) connecting said sealing finger (904) to said upstanding wall (3), said hinge (907) comprising a flattened portion (909) and said at least one lug (905) comprising a flattened section (910), said flattened portion (909) and said flattened section (910) cooperating to lock said sealing finger (904) in said second position.

36. The contamination prevention feature of claim 16, wherein:
in said first position, an outer surface (908) of said sealing finger (904) lies flush with an outer surface of said upstanding wall (3).

AMENDED CLAIMS

[received by the International Bureau on 15 January 1996(15.01.1996);
original claims 1-3, 7-10, 12, 16, 29 and 32- 36 amended;
new claims 37-92 added;
remaining claims unchanged (20 pages)]

1. A dispensing package comprising:
 - an integrally formed container portion (2) comprising:
 - a lower portion (16) and a retaining wall (10), said lower portion containing an open lower end, said lower end comprising a taper (18), said retaining wall comprising a retaining opening (11);
 - a pump structure (12), a circumferential outer surface of said pump structure being formed to be retained in said retaining opening (11) and sealed to said retaining wall (10); and
 - a one-piece bottom portion (17), said bottom portion (17) being formed separate from said container portion (2), said bottom portion (17) comprising a retaining groove (19), said retaining groove (19) being formed to receive said taper (18) to secure said bottom portion (17) to said lower end and seal said bottom portion to said lower end, whereby said container portion (2) can be filled with a liquid product through said open lower end and said bottom portion (17) sealed to said lower end to seal said liquid product within said container portion (2).
2. The dispensing package of claim 37, wherein:
 - said upstanding wall portion (3) comprises a groove (23) for retaining and sealing a nozzle (9) on said actuator portion (6), said upstanding wall (3) further comprising a limit stop (22) for preventing downward movement of said actuator portion (3) when said nozzle (9) is retained in said groove (23).
3. The dispensing package of claim 37, wherein:
 - said upstanding wall portion (3) comprises a removable tab (4) covering a dispensing opening (25) in said upstanding wall (3).
4. The dispensing package of claim 1, further comprising:

a shoulder (32) on said package (1) for supporting said package (1) during an assembly operation and a filling operation.

5. The dispensing package of claim 1, further comprising:

an energy director (15) for providing a seal between said retaining wall (16) and said pump structure (12).

6. The dispensing package of claim 1, further comprising:

an energy director (15) for providing a seal between said bottom portion (17) and said container portion (2).

7. A dispensing package comprising:

an integrally formed container portion (2) comprising:

a lower portion (16) and a retaining wall (10), said lower portion (16) comprising an open lower end (16), said lower end comprising a plurality of circumferentially spaced angled tabs (30), said retaining wall (10) comprising a retaining opening (11);

a pump structure (12), a circumferential outer surface of said pump structure (12) being formed to be retained in said retaining opening (11) and sealed to said retaining wall (10); and

a one-piece bottom portion (17), said bottom portion (17) being formed separate from said container portion (2), said bottom portion (17) comprising a retaining groove (19), said retaining groove (19) being formed to receive said angled tabs (30) to secure said bottom portion (17) to said lower end and seal said bottom portion (17) to said lower end, said angled tabs (30) cooperating with a horizontal portion (31) on said bottom portion (17), to thereby ensure that said bottom portion is secured horizontally to said container portion.

8. A method of providing a dispensing container comprising the steps of:
providing a package (2) comprising an open lower end (16) and a retaining wall (10) in an upper end, said retaining wall (10) comprising a retaining opening (11), said lower end (16) comprising a taper (18);
providing a pump structure (12);
inserting said pump structure (12) into said retaining opening (11);
filling said package (2) with a fluid product through said open lower end (16);
providing a one-piece bottom portion (17) comprising a retaining groove (19);
attaching said bottom portion (17) to said lower end (16) by inserting said taper (18) into said retaining groove (19); and
sealing said taper (18) against said groove (19) to thereby seal said fluid product in said package (2).
9. The method of claim 8, further comprising the steps of:
providing a spray actuator (6); and

inserting said spray actuator (6) on said pump structure (12).

10. A dispensing package comprising:

an integrally formed container portion (2) comprising:

a lower portion (16), a dip tube structure (160) and a retaining wall (10), said lower portion containing (16) an open lower end, said retaining wall (10) comprising a retaining opening (11), said dip tube structure (160) being integrally molded with said retaining wall (10);

a pump structure (12), a circumferential outer surface of said pump structure (12) being formed to be retained in said retaining opening (11) and sealed to said retaining wall (10); and

a bottom portion (17, 117, 217, 317), said bottom portion (17, 117, 217, 317) being formed separate from said container portion (2), said bottom portion (17, 117, 217, 317) being formed to be secured to said lower end and sealed to said lower end, whereby said bottom portion (17, 117, 217, 317) can be sealed to said lower end and said container portion (2) can be filled with a liquid product, to seal said liquid product within said container portion (2).

11. The dispensing package of claim 10, wherein:

said dip tube structure (160) comprises a vent hole (161).

12. A dispensing package comprising:
an integrally formed container portion (2) comprising:
a lower portion and a retaining wall (10), said lower portion containing an open lower end (16) and a retaining rim (284), said retaining wall (10) comprising a retaining opening (11);
a pump structure (12), a circumferential outer surface of said pump structure (12) being formed to be retained in said retaining opening (11) and sealed to said retaining wall (10); and
a bottom portion (117, 217), said bottom portion (117, 217) being formed separate from said container portion (2), said bottom portion (117, 217) being formed to be secured to said lower end (16) and sealed to said lower end (16), said bottom (117, 217) portion comprising a bottom portion inner sealing surface (280) sealable against an interior of said container portion (2), said bottom portion (117, 217) further comprising an outer retaining portion (286) engageable with said retaining rim (284), whereby said container portion (2) can be filled with a liquid product through said lower end (16) and said bottom portion (117, 217) sealed to said lower end (16) to seal said liquid product within said container portion (2).
13. The dispensing package of claim 12, wherein:
said bottom portion inner sealing surface (280) is tapered.

14. The dispensing package of claim 12, wherein:
said outer retaining portion (286) comprises snap fingers (288) engaging said retaining rim (284).
15. The dispensing package of claim 14, wherein:
said outer retaining portion (286) comprises a snap lip (287).
16. The dispensing package of claim 66, wherein:
said bottom portion (117, 217) comprises a stacking flange (393) engageable with said upstanding wall portion (3).
17. A dispensing package comprising:
an integrally formed container portion (2) comprising:
a lower portion and a retaining opening (11), said lower portion containing an open lower end (16);
a pump structure (12), a circumferential outer surface of said pump structure (12) being formed to be retained in said retaining opening (11); and
a bottom portion (17), said bottom portion (17) being formed separate from said container portion (2), said bottom portion (17) being formed to be secured to said open lower end (16) and sealed to said lower end (16), said bottom portion (17) comprising an integrally-formed dip tube (160), said dip tube comprising an least one opening (172) at an end of said dip tube adjacent said bottom portion (17), whereby said container portion (2) can be filled with a liquid product through said open lower end (16) and said dip tube (160) inserted through said open lower end (16) and said bottom portion (17) sealed to said lower end (17) to seal said liquid product within said container portion (2).
18. The dispensing package of claim 17, further comprising:
an insert (300), said insert being secured to an axially inward end of said pump (12).

19. The dispensing package of claim 18, wherein:
said insert (300) comprises an inlet passage (306), an outlet passage (308) and a valve (307), said valve (307) closing said inlet passage (306) in a non-inverted position of said dispensing package (1), said inlet passage (306) and said outlet passage (308) providing fluid communication between an interior of said package (1) and an interior of said pump (12) in an inverted position of said dispensing package (1).
20. The dispensing package of claim 18, wherein:
said insert (300) comprises a flared portion (303) adjacent a lower end of said pump (12), said flared portion (303) assisting insertion of an end of said dip tube (160) into said lower end of said pump (12).
21. A method of providing a dispensing container comprising the steps of:
providing a package (2) comprising an open lower end (16) and a retaining opening (11);
providing a pump structure (12);
inserting said pump structure (12) into said retaining opening (11);
filling said package (2) with a fluid product through said open lower end (16);
providing a bottom portion (17) with an integrally-formed dip tube (160);
inserting said dip tube (160) through said open lower end (16);
engaging an end of said dip tube (160) with said pump structure (12); and
attaching said bottom portion (17) to said open lower end (16) to thereby seal said fluid product in said package (2).
22. The method of claim 21, further comprising the step of:
inserting an insert (300) onto said lower end of said pump structure (12) after said step of inserting said pump structure (12) into said retaining opening (11).
23. An apparatus for securing a pump dispenser to a container comprising a retaining rim, said apparatus comprising:

a central opening (411), said central opening being shaped to receive an outer surface of said pump dispenser (12);

an inner sealing surface (283) sealable against an interior of said container (481);
and

an outer retaining portion (486) engageable with said retaining rim (484), said outer retaining portion (486) comprising a plurality of snap fingers (488) engageable with said retaining rim (484).

24. The apparatus of claim 23, further comprising:

a sealing finger (404, 604) pivotally mounted on an upstanding wall (403, 603), said sealing finger comprising a sealing rim (445).

25. The apparatus of claim 24, wherein:

said sealing finger (404, 604) pivots about a horizontal axis.

26. The apparatus of claim 24, wherein:

said sealing finger (404, 604) pivots about a vertical axis.

27. The apparatus of claim 24, further comprising:

a detent for retaining said sealing finger (404, 604) in a position away from said upstanding wall (403, 603).

28. The apparatus of claim 26, further comprising:

a hinge (441), said hinge comprising a radially projecting portion engageable with an actuator (6) to prevent rotation of said actuator (6).

29. A dispensing package comprising:

a pump dispenser (12), said pump dispenser (12) comprising an outer surface;

a container (402), said container (402) comprising an outlet opening, said container (402) further comprising an annular rim (484) surrounding said outlet opening, said outlet opening comprising an inner surface (481); and

a mounting device (417), said mounting device (417) comprising:

(a) a central opening (411), said central opening (411) being shaped to fixedly receive said outer surface of said pump dispenser (12);

(b) an inner sealing surface (483) sealable against said inner surface (481); and

(c) an outer retaining portion (486) engageable with said annular rim (484), said outer retaining portion (486) comprising at least one radially inward projection (488) engageable with said annular rim (484).

30. An apparatus for allowing inverted dispensing from a dispensing container comprising a dip tube, said apparatus comprising:

a first valve element (561, 562), said first valve element comprising first and second inlet openings and an outlet opening, said first valve element further comprising a gravity-biased check valve (563), said outlet opening of said first valve element receiving a lower end of said dip tube;

a tube (564), an end of said tube (564) being received in said second inlet opening of said first valve element (561, 562); and

a second valve element (565), said second valve element comprising an inlet opening, an outlet opening and a gravity-biased check valve (566), said outlet opening of said second valve element receiving another end of said tube (564).

31. A contamination prevention feature comprising:

an actuator (6) comprising a spray orifice and an orifice opening surrounding said spray orifice;

an upstanding wall (3) at least partially surrounding said actuator (6), said upstanding wall (3) further comprising a spray opening (25);

a sealing finger (404, 904), said sealing finger (404, 904) comprising an insert (445, 911), said insert (445, 911) being shaped to sealingly fit within said orifice opening, said sealing finger (404, 904) being pivotally mounted to said upstanding wall (3) so that in a first position of said sealing finger (404, 904) said insert sealingly fits within said orifice opening and covers said spray opening, and so that in a second position of said sealing finger (404, 904), said insert (445, 911) is spaced from said orifice opening and said sealing finger is spaced from said spray opening.

32. The contamination prevention feature of claim 31, wherein:
said sealing finger (404) pivots about a horizontal axis.
33. The contamination prevention feature of claim 31, wherein:
said sealing finger (904) pivots about a vertical axis.
34. The contamination prevention feature of claim 31, further comprising:
a hinge connecting (441) said sealing finger (404) to said upstanding wall (3), at least a portion of said hinge fitting in a recess (442) in said actuator (6) to thereby prevent said actuator (6) from rotating.
35. The contamination prevention feature of claim 31, further comprising:
a hinge (907) and at least one lug (905) connecting said sealing finger (904) to said upstanding wall (3), said hinge (907) comprising a flattened portion (909) and said at least one lug (905) comprising a flattened section (910), said flattened portion (905) and said flattened section (910) cooperating to lock said sealing finger (904) in said second position.
36. The contamination prevention feature of claim 31, wherein:
in said first position, an outer surface (908) of said sealing finger (904) lies flush with an outer surface of said upstanding wall (3).

37. The dispensing package of claim 1, further comprising:
an actuator portion (6) retained upon said pump structure (12), and wherein said integrally formed container portion (2) comprises an upstanding wall portion (3).
38. The dispensing package of claim 1, wherein:
said integrally formed container portion (2) comprises an upstanding wall portion (3).
39. The dispensing package of claim 1, further comprising:
an actuator portion (6) retained upon said pump structure (12).
40. The dispensing package of claim 39, further comprising:
a spring (50) mounted between said actuator portion (6) and said retaining wall (10).
41. The dispensing package of claim 7, wherein:
said integrally formed container portion (2) comprises an upstanding wall portion (3).
42. The dispensing package of claim 41, further comprising:
a spring (50) mounted between said actuator portion (6) and said retaining wall (10).
43. The dispensing package of claim 41, wherein:
said upstanding wall portion (3) comprises a groove (23) for retaining and sealing a nozzle (9) on said actuator portion (6), said upstanding wall (3) further comprising a limit stop (22) for preventing downward movement of said actuator portion (3) when said nozzle (9) is retained in said groove (23).
44. The dispensing package of claim 41, wherein:
said upstanding wall portion (3) comprises a removable tab (4) covering a dispensing opening (25) in said upstanding wall (3).

45. The dispensing package of claim 7, further comprising:
a shoulder (32) on said package (1) for supporting said package (1) during an assembly operation and a filling operation.
46. The dispensing package of claim 7, further comprising:
an energy director (15) for providing a seal between said retaining wall (16) and said pump structure (12).
47. The dispensing package of claim 7, further comprising:
an actuator portion (6) retained upon said pump structure (12).
48. The dispensing package of claim 47, further comprising:
a spring (50) mounted between said actuator portion (6) and said retaining wall (10).
49. The method of claim 8, wherein:
said step of inserting said pump structure (12) into said retaining opening (11) comprises inserting said pump structure (12) through said open lower end.
50. The method of claim 8, wherein:
said step of inserting said pump structure (12) into said retaining opening (11) comprises inserting said pump structure (12) from a side of said retaining wall (10) opposite said open lower end.
51. The dispensing package of claim 10, wherein:
said integrally formed container portion (2) comprises an upstanding wall portion (3).
52. The dispensing package of claim 51, wherein:
said upstanding wall portion (3) comprises a removable tab (4) covering a dispensing opening (25) in said upstanding wall (3).

53. The dispensing package of claim 51, further comprising:
a shoulder (32) on said package (2) for supporting said package (2) during an assembly operation and a filling operation.
54. The dispensing package of claim 51, further comprising:
an energy director (15) for providing a seal between said retaining wall (10) and said pump structure (12).
55. The dispensing package of claim 10, further comprising:
an actuator portion (6) retained upon said pump structure (12).
56. The dispensing package of claim 55, further comprising:
a spring (50) mounted between said actuator portion (6) and said retaining wall (10).
57. The dispensing package of claim 10, further comprising:
an actuator portion (6) retained upon said pump structure (12), and wherein said integrally formed container portion (2) comprises an upstanding wall portion (3).
58. The dispensing package of claim 57, wherein:
said upstanding wall portion (3) comprises a groove (23) for retaining and sealing a nozzle (9) on said actuator portion (6), said retaining wall (10) further comprising a limit stop (22) for preventing downward movement of said actuator portion (6) when said nozzle (9) is retained in said groove (23).
59. The dispensing package of claim 10, further comprising:
angled tabs (30) on said lower end of said container portion (2), said angled tabs (30) cooperating with a horizontal portion (31) on said bottom portion (17), to thereby ensure that said bottom portion (17) is secured horizontally to said container portion (2).

60. The dispensing package of claim 10, wherein:
said bottom portion (217) comprises a bottom portion inner sealing surface (280) sealable against an interior of said container portion (202), said bottom portion further comprising an outer retaining portion (286) engageable with a retaining rim (284) on said lower portion (16).
61. The dispensing package of claim 60, wherein:
said bottom portion inner sealing surface (280) is tapered.
62. The dispensing package of claim 60, wherein:
said outer retaining portion (286) comprises snap fingers (288) engaging said retaining rim (284).
63. The dispensing package of claim 62, wherein:
said outer retaining portion (286) comprises a snap lip (287).
64. The dispensing package of claim 10, further comprising:
an actuator portion (6) retained upon said pump structure (12).
65. The dispensing package of claim 64, further comprising:
a spring (50) mounted between said actuator portion (6) and said retaining wall (10).
66. The dispensing package of claim 12, wherein:
said integrally formed container portion (2) comprises an upstanding wall portion (3).
67. The apparatus of claim 23, further comprising:
said sealing finger (904) comprising a hinge (907), said hinge (907) comprising a flattened portion (909), said upstanding wall comprising lugs (905), said lugs (905) comprising a flattened section (910), said flattened portion (909) and said flattened section (910) cooperating, in one position of said sealing finger (904), to lock said sealing finger (904) in a position away from said upstanding wall.

68. The dispensing package of claim 29, wherein:
said inner sealing surface (483) is tapered.
69. The dispensing package of claim 29, wherein:
said at least one radially inward projection comprises snap fingers (488) engaging
said annular rim (484).
70. The dispensing package of claim 29, wherein:
said outer retaining portion (286) comprises a snap lip (287).
71. The apparatus of claim 30, wherein:
said second inlet opening of said first valve element (561, 562) and said outlet
opening of said first valve element (561, 562) are on one axial end of said first valve
element (561, 562), and wherein said first inlet opening of said first valve element (561,
562) is on an opposite axial end of said first valve element (561, 562).
72. A method of providing a dispensing container comprising the steps of:
providing a package (2) comprising an open lower end (16) and a retaining wall
(10) in an upper end, said retaining wall (10) comprising a retaining opening (11), said
lower end comprising a plurality of circumferentially spaced angled tabs (30);
providing a pump structure (12);
inserting said pump structure (12) into said retaining opening (11);
filling said package (2) with a fluid product through said open lower end (16);
providing a one-piece bottom portion (17) comprising a retaining groove (19) and
a horizontal portion (31); and
attaching said bottom portion (17) to said lower end by inserting said lower end
into said retaining groove (19) until said plurality of angled tabs (30) engage said
horizontal portion (31).
73. The method of claim 72, further comprising the steps of:
providing a spray actuator (6); and
inserting said spray actuator (6) on said pump structure (12).

74. The method of claim 72, wherein:

said step of inserting said pump structure (12) into said retaining opening (11) comprises inserting said pump structure (12) through said open lower end.

75. The method of claim 72, wherein:

said step of inserting said pump structure (12) into said retaining opening (11) comprises inserting said pump structure (11) from a side of said retaining wall (10) opposite said open lower end.

76. A dispensing package comprising:

an actuator portion (6) comprising a nozzle (9);

an integrally formed container portion (2) comprising:

an upstanding wall portion (3), a lower portion (16) and a retaining wall (10) comprising a retaining opening (11), said lower portion (16) containing an open lower end, said upstanding wall portion (3) comprising a groove (23) for retaining and sealing said nozzle (9) on said actuator portion (6);

a pump structure (12), a circumferential outer surface of said pump structure (12) being formed to be retained in said retaining opening (11) and sealed to said retaining wall (10); and

a one-piece bottom portion (17, 117, 217, 317), said bottom portion being formed separate from said container portion (2), said bottom portion (17, 117, 217, 317) being formed to be secured to said lower end and sealed to said lower end, whereby said container portion (2) can be filled with a liquid product through said open lower end and said bottom portion (17, 117, 217, 317) sealed to said lower end to seal said liquid product within said container portion (2).

77. The dispensing package of claim 76, wherein:

said retaining wall (10) further comprises a limit stop (22) for preventing downward movement of an actuator portion (6) when said nozzle (9) is retained in said groove (23).

78. The dispensing package of claim 76, wherein:

said upstanding wall (3) further comprises a bead (26), said bead (26) coacting with an outer surface of said actuator portion (6) to provide an audible sound when said nozzle (9) is retained and sealed in said groove (23).

79. A method of providing a dispensing container comprising the steps of:

providing a package (2) comprising an open lower end, a dip tube structure (160), and a retaining wall (10) in an upper end, said retaining wall (10) comprising a retaining opening (11), said dip tube structure (160) being integrally molded with said retaining wall (10);

providing a pump structure (12);

inserting said pump structure (12) into said retaining opening (11);

filling said package (2) with a fluid product;

providing a bottom portion (17, 117, 217, 317);

attaching said bottom portion (17, 117, 217, 317) to said lower end.

80. The method of claim 79, further comprising the steps of:

providing a spray actuator (6); and

inserting said spray actuator (6) on said pump structure (12).

81. A method of providing a dispensing container comprising the steps of:

providing a package (2) comprising an open lower end and a retaining wall (10) in an upper end, said retaining wall (10) comprising a retaining opening (11), said lower end comprising a retaining rim (284);

providing a pump structure (12);

inserting said pump structure (12) into said retaining opening (11);

filling said package (2) with a fluid product through said open lower end;

providing a one-piece bottom portion (117, 217, 317) comprising a bottom portion inner sealing surface (280) and an outer retaining portion (286); and

attaching said bottom portion (117, 217) to said lower end by sealing said bottom portion inner sealing surface (280) against an interior of said container portion and engaging said outer retaining portion (286) with said retaining rim (284).

82. The method of claim 81, further comprising the steps of:
providing a spray actuator (6); and
inserting said spray actuator (6) on said pump structure (12).
83. A dispensing package comprising:
an integrally formed container portion (102, 202, 302, 402) comprising an open end, said open end comprising a retaining rim (284, 484); and
a closure portion (117, 217, 317, 417), said closure portion (117, 217, 317, 417) being formed separate from said container portion (102, 202, 302, 402), said closure portion (117, 217, 317, 417) being formed to be secured to said open end and sealed to said open end, said closure portion (117, 217, 317, 417) comprising a closure portion inner sealing surface (280, 480) sealable against an interior of said container portion (102, 202, 302, 402), said closure portion (117, 217, 317, 417) further comprising an outer retaining portion (286, 486) engageable with said retaining rim (284, 484), whereby said closure portion (117, 217, 317, 417) may be sealed to said open end to seal liquid product within said container portion (102, 202, 302, 402).
84. The dispensing package of claim 83, wherein:
said closure portion inner sealing surface (280, 480) is tapered.
85. The dispensing package of claim 83, wherein:
said outer retaining portion comprises snap fingers (288, 488) engaging said retaining rim (284, 484).
86. The dispensing package of claim 85, wherein:
said outer retaining portion comprises a snap lip (287, 487).

87. A method of providing a dispensing container comprising the steps of:
providing a package (102, 202, 302, 402) comprising an open end, said open end comprising a retaining rim (284, 484);
providing a one-piece closure portion (117, 217, 317, 417) comprising a closure portion inner sealing surface (280, 480) and an outer retaining portion (286, 486); and
attaching said closure portion (117, 217, 317, 417) to said lower end by sealing said closure portion inner sealing surface (280, 480) against an interior of said container portion and engaging said outer retaining portion (286, 486) with said retaining rim (284, 484).
88. The method of claim 87, further comprising the steps of:
providing a spray actuator (6); and
inserting said spray actuator on said pump structure (12).
89. The dispensing package of claim 87, wherein:
said outer retaining portion (286, 486) comprises snap fingers (288, 488) engaging said retaining rim (284, 484).
90. The dispensing package of claim 89, wherein:
said outer retaining portion (286, 486) comprises a snap lip (287, 487).
91. A dispensing package comprising:
an integrally formed container portion (2) comprising:
a lower portion, said lower portion containing an open lower end, said lower end comprising an inset surface (281) on an inner circumference; and
a bottom portion (117, 217), said bottom portion (117, 217) being formed separate from said container portion (2), said bottom portion (117, 217) being formed to be secured to said lower end and sealed to said lower end, said bottom portion (117, 217) comprising a bottom portion inner sealing surface (280) sealable against an interior of said container portion (2), whereby said container portion (2) can be filled with a liquid product through said lower end and said bottom portion (117, 217) sealed to said lower end to seal said liquid product within said container portion.

92. The dispensing package of claim 91, wherein:
said bottom portion inner sealing surface is tapered.

1 / 2 2




FIG. 1

SUBSTITUTE SHEET (RULE 26)

2/22




FIG. 2a




FIG. 2b




FIG. 3a




FIG. 3b

3/22




FIG. 4

4 / 2 2




FIG. 6








FIG. 5






FIG. 11

SUBSTITUTE SHEET (RULE 26)

7/22




FIG. 12





FIG. 14

9/22




FIG. 15




FIG. 16

10/22




FIG. 17

11/22




FIG. 18

SUBSTITUTE SHEET (RULE 26)

12/22




FIG. 19

SUBSTITUTE SHEET (RULE 26)

13/22





FIG. 20

SUBSTITUTE SHEET (RULE 26)






FIG. 22




FIG. 23
SUBSTITUTE SHEET (RULE 26)

16/22




FIG. 24

SUBSTITUTE SHEET (RULE 26)

17/22




FIG. 25




FIG. 26




FIG. 27

18/22




FIG. 28
SUBSTITUTE SHEET (RULE 26)

19/22




FIG. 29




FIG. 30

20 / 22




FIG. 31

21/22




FIG. 32




FIG. 33




FIG. 34

22/22




FIG. 35




FIG. 36

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/05138

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :B65B 1/04, 3/04

US CL :Please See Extra Sheet.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 141/1,18,2,113; 222/321.7, 321.1, 321.4, 321.6, 402.19, 376, 556

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US, A, 5,085,350 (Sugita) 04 February 1992, see entire document.	1,2,4-6,12
Y		13
Y	US, A, 3,161,330 (Sagarin et al) 15 December 1964, see entire document.	13
X	US, A, 4,277,001 (Nozawa) 07 July 1981, see entire document.	30,31
A	US, A, 4,993,606 (Bolen, Jr. et al) 19 February 1991, see entire document.	all
A	US, A, 2,799,435 (Abplanalp) 16 July 1957, see entire document.	all

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	T	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	X	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	Y	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another claim or other special reason (as specified)	A	document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means		
P document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search
27 JUNE 1995

Date of mailing of the international search report
03 AUG 1995

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Authorized officer *Steven O. Douglas*
STEVEN O. DOUGLAS

Facsimile No. (703) 305-3230

Telephone No. (703) 308-0891

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US95/05138

A. CLASSIFICATION OF SUBJECT MATTER: US CL :

141/1,18,2,113; 222/321.7, 321.1, 321.4, 556

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.